

Maanori KUSUNOKI et al., S.N. 10/566,864  
Page 2

**RECEIVED**  
**CENTRAL FAX CENTER**

Dkt. 2271/75819

**Listing of Claims**

OCT 09 2007

The following listing of claims will replace all prior versions, and listings, of claims in the subject application:

1. (currently amended) A maintenance/recovery device for a liquid discharge device, comprising:

a cap member covering a surface of a nozzle of a liquid discharging head, the liquid discharging head discharging a droplet of a recording liquid from the nozzle;

a resilient contact member provided in the cap member to come in contact with the surface of the nozzle;

a recess-forming member providing in the cap member to form a recess for receiving the recording liquid attracted from the nozzle,

wherein the contact member and the recess-forming member are integrally formed by molding, the recess-forming member is made of a water-repellant resin material containing a water repellent agent, and the recess-forming member is provided to have at least two slopes being inclined toward an outlet at a bottom of the recess.

2. (original) The maintenance/recovery device according to claim 1 wherein a content of the water repellent agent in the resin material which forms the recess-forming member does not exceed 10 weight percent.

3. (original) The maintenance/recovery device according to claim 1 wherein the recess of the recess-forming member is provided with corners which are curved.

Maanori KUSUNOKI et al., S.N. 10/566,864  
Page 3

Dkt. 2271/75819

4. (original) The maintenance/recovery device according to claim 1 wherein a sum of an inclination angle of the slopes of the recess-forming member to a horizontal surface and a contact angle between the slopes and the recording liquid is 70 degrees or more.

5. (original) The maintenance/recovery device according to claim 4 wherein the sum of the inclination angle and the contact angle is 90 degrees or more.

6. (currently amended) An image forming device comprising:

a liquid discharge head provided as a recording head which discharges a droplet of a recording liquid from a nozzle; and

a maintenance/recovery device provided to maintain and recover performance of the liquid discharge head,

the maintenance/recovery device comprising:

a cap member covering a surface of the nozzle of the liquid discharging head;

a resilient contact member provided in the cap member to come in contact with the surface of the nozzle;

a recess-forming member providing in the cap member to form a recess for receiving the recording liquid attracted from the nozzle,

wherein the contact member and the recess-forming member are integrally formed by molding, the recess-forming member is made of a water repellent resin material containing a water repellent agent, and the recess-forming member is provided to have at least two slopes being inclined toward an outlet at a bottom of the recess.

Maanori KUSUNOKI et al., S.N. 10/566,864  
Page 4

Dkt. 2271/75819

7. (original) The image forming device according to claim 6 wherein the recording liquid contains a water, a pigment of 6 weight percent or more, a polymer component, and a water-soluble organic solvent, and the recording liquid has a surface tension of 40 mN/m or less at 25 degrees C and has a viscosity that is above 5 cp and below 20 cp at 25 degrees C.

8. (original) The image forming device according to claim 6 wherein a content of the water repellent agent in the resin material which forms the recess-forming member does not exceed 10 weight percent.

9. (original) The image forming device according to claim 6 wherein the recess of the recess-forming member is provided with corners which are curved.

10. (original) The image forming device according to claim 6 wherein a sum of an inclination angle of the slopes of the recess-forming member to a horizontal surface and a contact angle between the slopes and the recording liquid is 70 degrees or more.